

**WEST**

Generate Collection

Print

L3: Entry 2 of 3

File: EPAB

Jun 15, 1989

PUB-NO: DE003741364A1  
DOCUMENT-IDENTIFIER: DE 3741364 A1  
TITLE: Pneumatic booster

PUBN-DATE: June 15, 1989

## INVENTOR-INFORMATION:

NAME

REGEL, MATHIAS

COUNTRY

DE

## ASSIGNEE-INFORMATION:

NAME

HONEYWELL REGELSYSTEME GMBH

COUNTRY

DE

APPL-NO: DE03741364

APPL-DATE: December 7, 1987

PRIORITY-DATA: DE03741364A (December 7, 1987)

INT-CL (IPC): F15B 3/00

EUR-CL (EPC): G05D016/16

## ABSTRACT:

CHG DATE=19990617 STATUS=O> In a pneumatic booster, the chamber counteracting the inlet control pressure (pk) is subdivided into two chambers (24, 26) by a partition wall (16). A double cone (32) is guided with its shank (34) in a sealed-off manner in the partition wall (16). The lower chamber (26) is connected to the outlet via a channel (54), and a bore (52) connects this channel (54) to the chamber (24) located above. When the incoming air (Z) is allowed through to the outlet (Y), a negative pressure occurs in the chamber (24) via the bore (52), so that, in the event of an abrupt rise in the inlet control pressure, the booster does not tend to overshoot

(Fig. 1).

